

MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT lbs/kg	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
<b>WaterMaster</b>									
WM 1200	18053	144/366	24/61	24/61	28.5/72	250/113	CF Opt/Opt Imm & Self Reg Heat Cbl	60/227	500 beef, 250 dairy
WM 96	18007	96/244	33/84	22/56	28/71	200/91	CF Std/Opt Imm & Self Reg Heat Cbl	75/284	300 beef, 150 dairy
WM 90	16467	90/229	33/85	22/56	28/71	180/82	CF Std/Opt Imm & Self Reg Heat Cbl	30/114	300 beef, 150 dairy
WM 600	18171	72/183	24/61	24/61	28.5/72	140/64	CF Opt/Opt Imm & Self Reg Heat Cbl	28/106	250 beef, 125 dairy
WM 54	16542	54/137	33/87	22/56	28/71	125/57	CF Std/Opt Imm & Self Reg Heat Cbl	18/68	200 beef, 100 dairy
Deep 54	18355	54/137	33/84	28/71	22/56	125/57	CF Std/Opt Imm & Self Reg Heat Cbl	54/204	200 beef, 100 dairy
<b>WaterMatic</b>									
1000	18110	42/107	42/107	26/66	26/66	120/54	Opt Imm & Self Reg Heat Cbl	22/83	275 beef, 135 dairy
300	18050	36/91	21.5/55	26/66	26/66	69/31	Opt Imm & Self Reg Heat Cbl	8.2/31	125 beef, 60 dairy
150S	18222	33.5/85	14/36	13/33	13/33	39/18	Opt Imm & Self Reg Heat Cbl	4.2/16	100 sheep or goats
150	18166	33.5/85	14/36	18/46	18/46	47/21	Opt Imm & Self Reg Heat Cbl	4.2/16	40 beef, 40 horses
100	18165	24.5/62	14/36	18/46	18/46	36/16	Opt Imm & Self Reg Heat Cbl	2.8/11	20 beef, 20 horses
<b>Thrifty King</b>									
CT6	16440	72.5/184	39/99	19/48	25/64	210/95	Opt Imm & Self Reg Heat Cbl	55/208	300 beef
CT4-2000	16430	42.8/109	35/89	19/48	25/64	152/69	Opt Imm & Self Reg Heat Cbl	45.5/172	200 beef
CT2-2000	16299	42.8/109	24/61	19/48	25/64	90/41	Opt Imm & Self Reg Heat Cbl	28/106	100 beef
CT1-2000	16271	28/71	20.3/51	19/48	25/64	53/24	Opt Imm & Self Reg Heat Cbl	11.2/42	30 beef
<b>OmniFount</b>									
MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT lbs/kg	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
Omni 5	16745	40/102	23.5/60	26/66	26/66	88/40	Standard Electric 548W (4.6A@120V)	16/61	150 beef, 75 dairy
Omni 3	18270	31.5/80	22/56	26/66	26/66	75/34	Standard Electric 548W (4.6A@120V)	10./38	100 beef, 50 dairy
Omni 2	16619	28.3/72	14.5/37	18/46	18/46	45/20	Standard Electric 298W (2.5A@120V)	2.2/8	40 horses, 40 beef
Omni 1	18359	20/51	14.5/37	26/66	18/46	18/46	Standard Electric 173W (1.4A@120V)	1.5/6	20 Horses or beef
<b>CattleMaster</b>									
CM 1440	18252	145.5/396.6	23.5/59.7	16/41	26/66	272/123	Std Elec or CF 1298W (10.9A@120V)	60/227	475 beef, 240 dairy
CM 840	18235	86/218.4	23.5/59.7	16/41	26/66	130/64	Std Elec or CF 1048W (8.8A@120V)	35/133	300 beef, 150 dairy
CM 480	18248	51/129.5	23.5/59.7	16/41	26/66	90/41	Std Elec or Cf 548W (4.6A@120V)	20/76	200 beef, 100 dairy
<b>Cattle Fountain</b>									
5E	16745	38.4/98	20.1/51	26/66	30/76	101/46	Std Elec/Opt Gas 548W (4.6A@120V)	16/61	150 beef, 75 dairy
3E	16743	29.6/75	18/46	26/66	30/76	82/37	Std Elec/Opt Gas 548W (4.6A@120V)	10/38	100 beef, 50 dairy
<b>Combination Fountain</b>									
3 Combo.	16769	29.6/75	18/46	26/66	30/76	100/45	Std Elec/Opt Gas 798W (6.7A@120V)	10/38	100 beef, 80 hogs
<b>AC Series</b>									
MODEL	PART #	LENGTH in/cm	WIDTH in/cm	HEIGHT lbs/kg	Overall Height	WEIGHT lbs/kg	HEAT	CAPACITY gal/liter	HERD CAPACITY
2AC	18033	25.9/66	11.4/29	17.8/45	21.5/55	38/17	Standard Electric 298W (2.5A@120V)	2.2/8	40 beef, 80 calves
1AC	18034	17.6/45	11.4/29	17.8/45	21.5/55	28/13	Standard Electric 298W (2.5A@120V)	1.5/6	20 beef, 40 calves
2AC Special	18043	25.9/66	11.4/29	10.8/27	14.5/37	30/14	Standard Electric 298W (2.5A@120V)	2.2/8	40 beef, 80 calves
<b>Commander Series</b>									
Comm. 2	16758	32.7/83	17/43	16/41	16/41	68/31	Standard Electric 298W (2.5A@120V)	6.5/25	60 beef
Comm. 1	16751	20.1/51	17/43	16/41	16/41	41/19	Standard Electric 173W (1.4A@120V)	3.5/13	30 beef
<b>Stall Fount</b>									
Stall Fount 125	18082	14/36	13/33	Adjust.	Adjust.	31/14	Standard Electric 173W (1.4A@120V)	1.9/7	single stall
Stall Fount	16871	14/36	13/33	Adjust.	Adjust.	13/6	NA	1.9/7	single stall
Shroud Set	18092	19.4/49 each	18-Jul	Up to 4'		16/7	NA	NA	NA
<b>Pork King</b>									
PK 4	16459	31.5/80	23.3/59	7in/18cm	12.5/32	63/29	Standard Electric 548W (4.6A@120V)	3.5/13	160 hogs
PK 2-1	16458	23.2/59	23.3/59	7in/18cm	12.5/32	50/23	Standard Electric 298W (2.5A@120V)	2/8	80 hogs
PK 2	16457	31.5/80	13/33	7in/18cm	12.5/32	42/19	Standard Electric 298W (2.5A@120V)	2/8	80 hogs
PK 1	16456	23.2/59	13/33	7in/18cm	12.5/32	30/14	Standard Electric 298W (2.5A@120V)	1.2/5	40 hogs
<b>Thrifty King for Swine</b>									
HG 4	16260	31.3/80	31.3/80	8in/20cm	16/41	70/32	Opt Imm & Self Reg Heat Cbl	5.2/20	160 hogs
HG 2	16259	31.3/80	20/51	8in/20cm	16/41	50/23	Opt Imm & Self Reg Heat Cbl	2/8	80 hogs